



Micro Gum

Product Id: MG-3540-FH

MG-3540-FH is a fine white to pale yellow powder having high viscosity, used in Oil Drilling due to fast hydration. Product Specification ensured by MICRO GUM is as follows:

Application:

Oil & Gas Well Drilling, Diesel Slurry

Chemical Analysis:-

MOISTURE	8 % Maximum
ASH	1 % Maximum
pH	7-8

Granulation:-

ON 40 #	Nil
ON 200 #	TRACES

FANN Viscosity:-

VISCOCITY IN 2% KCL SOL. AT GRACE M3600 VISCOMETER AFTER 3 MINUTE ON 300 RPM AT 25° C (STIRRING AT 1500 RPM FOR TWO & HALF MINUTES IN WARRING BLENDER)

3 Minutes	35 CPS Min.
60 Minute	40 CPS Min.

Packing:-

25 Kg / 50 LBS, Multiwall Paper Bag with inside Polyliner / Laminated (Paper Bag Size 32")/Or
1000 Kg / 500 Kg Jumbo bags Or as per Buyer's Requirement

Reg.Office Address :- 44, Gokuldharm Society, Nr.Smurti Mandir, Ghodasar, Ahmedabad-50, Gujarat (India)

Plant Address:- Plot no.-104, G.I.D.C. Siddhpur,Tal. Siddhpur, Dist. Patan – 384130.Gujarat (India).

E-mail :- microgum@yahoo.com , info@microgum.net, microgum@gmail.com

Website:- www.microgum.net , www.guargumpowderindia.com

Tel No:- 079-25855879 Fax No:- 079-25855992 Mob.: +91 9824024233 / +91 9824047233